

N3CS2

2 Mpx Box Mini network camera

KEY FEATURES

- 2 Megapixel resolution
- SD card slot for local alarm recording
- 2.8mm Board lens
- Low bitrate, Excellent low light performance
- d-WDR, 2D/3D DNR, ROI, Defog, Privacy mask
- Onvif 2.4 compliant



◆ TECHNICAL SPECIFICATIONS

Camera	
Image Sensor	IMX290
Main processor	Hi3516D
Resolution	1080P
Effective Pixels	1945(H)*1097(V)
Compression	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Audio	NO
Alarm	NO
SD Card	support 128G Micro SD
Video Output	Network
Lens	
Focus Length	Board Lens 2.8mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	3Mp
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	YES, Support IEEE 802.3af
WIFI	NO
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@30fps
Browser	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands
General	
Housing	Metal
IR Cut Filter	NO
Operation Temperature	-20 ~ +60 RH95% Max
Storage Temperature	-20 ~ +60 RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	36(W) x 36(H) x33(D)mm
Weight	300g

IP

2 YEARS WARRANTY

ONVIF

DATA SHEETS

N3CS2

2 Mpx Box Mini network camera

MECHANICAL DRAWINGS

