

DIGIEYE 2A



Channels
BCN inputs
IP camera inputs
Display output
BNC outputs (analog video only)
BNC composite video outputs (analog and IP multi-split video)
Analog max.resolution
Analog Frame rate (4CIF PAL)
AHD max. resolution
IP max. resolution
Bitrate IP (input)
Video compression (analog)
Video compression AHD/IP
Camera configurable parameters
Network
Inputs/Outputs dry contacts-outputs relais
Additional Inputs/Outputs
IP camera digital input (ONVIF)
Serial
USB
Cooling
Recording mode
Motion detection
CPU
RAM
Operating system
Internal storage
PTZ Control
Bi-directional audio
Remote management systems
Remote view/control
Mobile App
Rack mount
Power supply
BxHxD (mm)- Weight

DVR			HVR			NVR		
4	8	16	4	8	16	4	8	16
√ CVBS AHD (opt.)	√ CVBS AHD (opt.)	√ CVBS AHD (opt.)	√ CVBS AHD (opt.)	√ CVBS AHD (opt.)	√ CVBS AHD (opt.)			
			√ ONVIF	√ ONVIF	√ ONVIF	√ ONVIF	√ ONVIF	√ ONVIF
2x Full HD (VGA + HDMI independent)								
4x independent								
Option (SY-DGI-CVBS-OUT)								
704x576 (4CIF)								
400 IPS								
3 MegaPixels (1920 x 1536)								
4 MegaPixels (2688 x 1520)								
4 Mbit/s per camera 80 Mbit/s total								
DELTA - property of Syac-TB								
H.264 (with variable parameters)								
Frame-rate, Resolution, compression rate								
2x Gigabit Ethernet								
18/18						4 / 2		
Option (SY-NET-IO-CONTROLLER)								
24 additional connections I/O up to 64 / 64 total by system								
			√	√	√	√	√	√
2x RS485/RS232								
2x USB 2.0 - Front 2x USB 3.0 + 2x USB 2.0 - Back								
Fanless								
Manual / Scheduled / Alarmed								
96x64 motion areas matrix 6 motion sensitivity levels 16 PTZ presets								
AMD GE-420 Quad-core 2.0 GHz								
2 GB DDR3-1600								
Syac-TB DigiEye (Linux)								
1x HDD 3.5" 500 GB / 1 TB / 2 TB / 4 TB / 8 TB								
Analog speed-dome			Analog and IP Speed-dome			IP Speed-dome		
√	√	√	√	√	√	√	√	√
DCC Lite / DCC Premium								
web, multi-platform viewer (PC/MAC/ Linux)								
iOS / Android								
Optional rack support with handles (SY-3A-RACK-K00)								
DC 9-30 V External								
88 x 432 x 210 mm (17" rack 2U) - 7 kg								

for more information, write to info.syac@techboardgroup.com